



































































Liquid Inks & Coatings Product Selection Guide

 **Highly Recommended**
Recommended

		S232	S363	S381	S379 H	S394	S395	S483	NT 5223	NS 59	FS 225	FS 421	FS 515	FS 893A	SST2	AQ 52	AQ 178G	H257	H303	
Properties	Product Type	Micronized Powder													Dispersions					
	Active Component	Wax	Wax	Wax	Wax	Wax	Wax	Wax	Wax	PP	Wax/PTFE	Wax/PTFE	Wax/PTFE	Wax/PTFE	PTFE	PTFE	Wax/PTFE	Wax	Wax	
	Solid Content (%)	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	60	52	45	35
	Wax Melting Point (°C)	110	140	98	97	112	125	113	104	150	100	112	120	110	320	320	110	100	100	
	Particle Size, MV (µm)	3-4	4-6	5-9	8-10	5-9	4-1	7-9	8-10	7-9	9	5-7	7-9	4-6	6-8	3-5	5-7	10	12	
	NPIRI Grind	2.5	2.5	2.5	5	2.5	2.5	5	5	6.5	5	2.5	4	3	3.5	2.5	5	4	7-9	
Performance Benefits	Rub Resistance																			
	Wet Rub Resistance																			
	Slip																			
	Anti-Slip																			
	Gloss Retention																			
	Gloss Reduction																			
	Recoatability																			



ISO 9001:2008 CERTIFIED FACILITIES:

Newark, NJ • Henderson, KY
Tianjin, China • Tongeren, Belgium

www.shamrocktechnologies.com

