

AquaFLON® 52

PTFE Aqueous Dispersion

The AquaFLON® product line is comprised of aqueous dispersions of PTFE or PTFE with wax. These products are designed for stability, pourability and easy incorporation into water based systems. They are used as additives to provide slip and abrasion resistance.

Product Description:

AquaFLON[®] 52 is a nonionic aqueous dispersion of polytetrafluoroethylene (PTFE).

Application:

AquaFLON® 52 is recommended for flexographic and gravure water-based inks and specialty coatings. It is used at 1-5% of the total formula weight.

Features and Benefits:

Rub and Abrasion Resistance

Slip (Low COF)

High Temperature Resistance

Broad Chemical Resistance

Typical Properties:

White Thick Liquid Appearance:

NPIRI Grind: 2.0 max MV: 4 µm

Weight/Gallon: 11.0 - 12.0 lbs/gal Viscosity: 1,500 - 2,500 CPS

% Non Volatile: 57 - 63 7 - 8 pH:

Regulatory Status:

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS. This product meets the requirements of 21 CFR 175.105, 175.300, 176.170, and 176.180.

Safety, Shipping and Handling:

Precautions: **Keep from freezing**.

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For more information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com..

Corporate Headquarters Foot of Pacific Street Newark, NJ 17114 Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822

Tongeren, Belgium Heersterveldweg 21, Phone: +32 1245 8330

Tianjin, China Fty 5, Ave. 9, TEDA B-3700 Tongeren Belgium Phone: +86 22 5981 3085