

# FluoroSPERSE® 153V

**PTFE Dispersion** 

Shamrock offers dispersions of PTFE that may be poured directly from the drum into the mixing container. They assure good wetting, uniform composition, and avoid the handling of powder. They are available in a range of printing ink vehicles, solvents, and in combination with wax.

## **Product Description:**

FluoroSPERSE<sup>®</sup> 153V is a dispersion of polytetrafluoroethylene (PTFE) micropowder in a universal lithographic system.

# Application:

FluoroSPERSE $^{\odot}$  153V is recommended for offset and heat set lithographic inks at 1 – 4% of the total formula weight.

#### **Features and Benefits:**

Rub Resistance

Slip (Low COF)

Ease of Incorporation

# **Typical Properties:**

NPIRI Grind: 2.5 Max

★ Weight/Gallon: 9.8 – 10.8 Lbs / Gal

## **Regulatory Status**

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

### Safety, Shipping and Handling

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822

Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085





Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822

Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085