

FluoroSPERSE® 7908

PTFE Dispersion

Shamrock offers dispersions of PTFE that may be poured directly from the drum into the mixing container. They assure good wetting, uniform composition, and avoid the handling of powder. They are available in a range of printing ink vehicles, solvents, and in combination with wax.




Product Description:

FluoroSPERSE® 7908 is dark colored dispersion of polytetrafluoroethylene (PTFE) micropowder in a general use lithographic varnish.

Application:

FluoroSPERSE® 7908 is widely used in the offset ink industry. It is recommended for heatset inks at 2 – 4% of total formula weight.

Features and Benefits:

-  Rub Resistance
-  Slip (Low COF)
-  Ease of Incorporation

Typical Properties:

-  NPIRI Grind: 2.5 Max

Regulatory Status

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

Safety, Shipping and Handling

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY
301 Community Drive
Henderson, KY 42420
Phone: +1(800)349-1822

Tongeren, Belgium
Heersterveldweg 21,
B-3700 Tongeren Belgium
Phone: +32 1245 8330

Tianjin, China
Fty 5, Ave. 9, TEDA
Phone: +86 22 5981 3085