
TexMATTE 6017

Polymethyl Methacrylate Powder






Product Description:

TexMATTE 6017 is a cross-linked polymethyl methacrylate product.





Application:

TexMATTE 6017 is used in both liquid and offset inks as well as UV coatings at a recommended level of 5.0 – 15.0% of the total formula weight.

Features and Benefits:

-  Abrasion Resistance
-  Mar / Scuff
-  Anti-Slip
-  Matting
-  Texture

Typical Properties:

 Appearance:	Free-Flowing White Powder
 Specific Gravity:	1.2 g/cm ³
 Particle Size Mean Value:	19 µm
 99% of Particle Under:	40 µm

Regulatory Status

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS. This product meets the requirements of 21 CFR 175.105, 175.300, 176.180, 177.1010, 177.1520, and 178.3790.

Safety, Shipping and Handling

For complete shipping, handling, health and safety information please contact your regional Customer Service Representative. Please contact them at your convenience for instructions and Material Safety Data Sheets, the contact information is located below.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY
301 Community Drive
Henderson, KY 42420
Phone: +1(800)349-1822

Tongeren, Belgium
Heersterveldweg 21,
B-3700 Tongeren Belgium
Phone: +32 1245 8330

Tianjin, China
Fty 5, Ave. 9, TEDA
Phone: +86 22 5981 3085