

NanoFLON® 160G-RC

PTFE Micropowder

Product Description:

NanoFLON® 160G-RC is a low molecular weight PTFE that consists of loose agglomerates of primary particles. The high surface area of these free-flowing powders makes them efficient thickeners. Its small primary particle size allows it to fit between "point" contacts between mating surfaces, and into small asperities, to prevent wear, and improve release properties. It is produced to be in compliance with EU regulatory requirements.

Application:

NanoFLON® 160G-RC is suitable for greases and lubricants made for mil-spec, automotive, aerosol, and other industrial applications such as thin film coatings.

Features and Benefits:

💝 High Surface Area

Reduce Wear and Noise

Typical Properties:

Appearance

White Powder

Particle Size Mean Value

< 6 µm < 0.8 µm

Primary Particle Size

 $9 - 15 \text{ m}^2/\text{g}$

Specific Surface Area

9 - 1511179

DSC Melting Point

325 – 330 °C

Regulatory Status

This product is NSF-registered for HX-1 and HX-2 uses. The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS. This product complies with the Commission Delegated Regulation (EU) 2020/784 on PFOA and (EU) 2021/1297 on C9-C14 (per Shamrock QSOP-202E and QSOP-205E).

Safety, Shipping and Handling

For complete safety, shipping and handling information, please refer to the product SDS, contact your regional Customer Service Representative, or contact our Customer Service Team by e-mail at customerserviceteam@shamrocktechnologies.com.

For more information about Shamrock's other products, please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822

Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085