

# NonSKID 8001

Wax Powder

Shamrock's NonSKID micropowders provide resistance to sliding forces.

## **Product Description:**

NonSKID 8001 is a combination of micronized polypropylene and PTFE.

### Application:

NonSKID 8001 is suitable for water and solvent applications, such as, high performance packaging coatings and high end wood coatings. NonSKID 8001 is an easily dispersible powder providing excellent hardness of the final coating.

#### **Features and Benefits:**

Scratch Resistance

Grip/Traction

Controlled COF

High-Temperature Resistance

#### **Typical Properties:**

Appearance: Off White Powder

Particle Size Mean Value: 7-9 µm
NPIRI Grind: 6.5 Max

DSC Melting Point: 302 °F /150°C
DSC 2<sup>nd</sup> Melt Point: 608 °F /320°C

#### **Regulatory Status:**

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

#### Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 **Tianjin, China** Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085



# Technical Data

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 **Tianjin, China**Fty 5, Ave. 9, TEDA
Phone: +86 22 5981 3085