



S-379-N8

Synthetic Wax Powder

Shamrock's product line of micronized waxes provide rub and abrasion resistance. Included in this line are products that provide gloss, matting, clarity, and controlled slip in a range of particle sizes.

Product Description:

S-379-N8 is a synthetic wax with a DSC peak melt above 100°C and corresponding low onset of melting.

Application:

S-379-N8 is recommended for use in water-based and general purpose industrial coatings at 2-3% of total formula weight. S-379-N8 is recommended for powder coatings as a slip and degassing agent.

Features and Benefits:

Slip (Low COF)

Rub and Mar/Scuff Performance

Gas Release (Powder Coatings)

Gloss Retention

Typical Properties:

Specific Gravity: 0.93 g/cm³
Particle Size Mean Value: 11 μm
99% of Particle Under: 40 μm
Hegman Grind: 5.0 Min

Melting Point: 212 / 100 °F / °C

Regulatory Status:

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085