

# S-394 MG

Polyethylene Wax Powder

# **Product Description:**

S-394 MG is a fine particle size, polyethylene wax powder.

# Application:

S-394 MG provides excellent rub/abrasion resistance to liquid inks, paste inks and thin-film coatings. It has a high onset of melting, which leads to insolubility and, in inks, excellent imprintability and freedom from overprint varnish "crawling."

#### **Recommended Level:**

1.0 – 2.0% of total formula weight for liquid inks

2.0 - 3.0% for paste inks and coatings

(Too much S-394 MG will cause gloss reduction.)

#### **Features and Benefits:**

As part of the S-Series waxes, S-394 MG also features:

**Excellent Recoatability** 

Consistently Narrow Particle Size Distribution

Compatibility With PTFE (0.5 - 1.0% SST-4 with 2 - 2.5% S-394 MG Recommended For Enhanced Rub Resistance)

Easy Dispersion With Mild Agitation (or High Speed Mixing Equipment)

### **Typical Properties:**

Off White Powder Appearance: Specific Gravity: 0.95 q/cm3 Particle Size Mean Value:  $3-4 \mu m$ 99% of Particle under: 12 µm NPIRI Grind: 2.0 Max Heaman Grind: 6.75 Min **DSC Melting Point:** 235°F / 113°C

#### **Regulatory Status**

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

# Safety, Shipping and Handling

For complete shipping, handling, health and safety information please contact your regional Customer Service Representative. Please contact them at your convenience for instructions and Material Safety Data Sheets, the contact information is located below.

**Corporate Headquarters** Foot of Pacific Street Newark, NJ 17114 Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822

Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +86 22 5981 3085 Phone: +32 1245 8330

Tianjin, China Fty 5, Ave. 9, TEDA