



# S-400-N1

#### Micronized EBS Wax

Shamrock's product line of micronized waxes provide rub and abrasion resistance. Included in this line are products that provide gloss, matting, clarity, and controlled slip in a range of particle sizes.

## **Product Description:**

S-400-N1 is micronized EBS (ethylene bis stearamide) wax powder showing melting peaks ranging from 99 – 147°C.

# Application:

S-400-N1 is used in both the ink and coating industry. S-400-N1 is recommended for powder, water- based, solvent-based, and UV systems at 1-2% of the total formula weight.

S-400-N1 also acts as a defoamer.

#### **Features and Benefits:**

Slip (Low COF)

Release

# **Typical Properties:**

Specific Gravity: 0.98 g/cm³
Particle Size Mean Value: 5 μm
99% of Particle Under: 15 μm
NPIRI Grind: 2.5 Max
Hegman Grind: 6.0 Min

# **Regulatory Status:**

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

## Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085