

TexMATTE 6010

Polymethyl Methacrylate Powder

Shamrock's Texture Series consists of polyethylene, polypropylene, polytetrafluoroethylene (PTFE), and PMMA (Texture-W, SPP, FluoroTEX, TexMATTE) powders in a controlled range of particle sizes. These stir in powders provide a unique feel and texture allowing for customized surface finishes.

Product Description:

TexMATTE 6010 is a cross-linked polymethyl methacrylate product.

Application:

TexMATTE 6010 is used in both liquid and offset inks as well as UV coatings at a recommended level of 5.0-10.0% of the total formula weight.

Features and Benefits:

Abrasion resistance

Mar/scuff

Anti-slip

Matting

Texture

Typical Properties:

Appearance: Free-Flowing White Powder

Specific Gravity: 1.2 g/cm³
Particle Size Mean Value: 10 μm
99% of Particle Under: 25 μm

Regulatory Status:

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS. This product meets the requirements of 21 CFR 175.105, 175.300, 176.180, 177.1010, 177.1520, and 178.3790.

Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085