

# **Texture 5380 White**

Polyethylene Powder

Shamrock's Texture Series consists of polyethylene, polypropylene, polytetrafluoroethylene (PTFE), and PMMA (Texture-W, SPP, FluoroTEX, TexMATTE) powders in a controlled range of particle sizes. These stir in powders provide a unique feel and texture allowing for customized surface finishes.

## **Product Description:**

Texture 5380 White consists of premium grade crystalline polyethylene.

## Application:

Texture 5380 White is used in air dry and baked coatings at a recommended level of 5.0-15.0% of the total formula weight. This product can be used in solvent, aqueous, and UV systems.

#### **Features and Benefits:**

Texture

Abrasion Resistance

Mar/Scuff

Anti-Slip

Matting

## **Typical Properties:**

Particle Size Mean Value: 65 μmScreen Size: 230 Mesh

### **Regulatory Status:**

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

## Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 07114
Phone: +1(800)349-1822

Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085